



# Textura® Recycled



#### **DOMESTIC**

Tile Dimension 53-1/2" x 13-1/2"
Tile Depth 3/8"
Coverage per box 5.01 sq.ft.
Weight per tile 6 lbs.



#### **JUNGLE**

Tile Dimension 60" x 12"
Tile Depth ½"
Coverage per box 6
Weight per tile 7 lbs

#### **Product Overview**

**Textura® Recycled** is an interlocking wood wall panel made using wood strips of varying length and height to create a natural wood, staggered edged panel that is seamless when installed. The strips come in three different heights, each with a different thickness, creating a panel with relief and dimension. The **DOMESTIC** series uses sustainably harvested North American species. The **JUNGLE** series uses 'mixed' species within each strip, for a more complex visual and color variation.

## **Specifications**

**Description:** Staggered edge interlocking wood panels made from sustainably sourced wood strips from other post-industrial applications.

Version (select one): Domestic, Jungle

**Domestic Color (select one):** Walnut, Cuban Oak, Mossy Maple

**Jungle Color (select one):** Jungle Light, Jungle Medium, Jungle Dark

Composition: Wood Strips on multiply wood backer


**Fire-rating:** Class "C" (Note: considered Class "B" in 'sprinkled' assemblies)

**Installation:** Direct applied with Wakol Loba MS262 (construction adhesive)

#### Colors

#### **Domestic Colors**







Cuban Oak

Mossy Maple

#### Jungle Colors







Light Medium

Dark





### Sustainable Attributes

**Environmental Certification** 

- Made with natural and sustainably sourced wood.
- Provides a true wood aesthetic using resources as efficiently as possible.
- Lightweight panels allow for ease of handling, and minimal use of fasteners (or glue) to apply.
- Contains NO Toxins and is VOC-free
- Sustainable supply chain
- Declare Red List free
- ISO 14001 Certified Environmental Management
- North American species Manufacturing

Installation adhesive certifications (with recommended: Wakol Loba MS262)

- Floor Score certification
- ECl Certification
- Bay Area Air District compliance (BBAQMD -Regulation 8, Rule 51)
- South Coast Air Quality Management District compliance (SCAQMD- Rule 1168)

## **Green Building Certification**

Sustainable Materials products meet criteria for WELL, LEED, Green Star, and BREEAM building rating systems, helping you achieve certification for your project. For support and guidance on available rating system points please visit www.SustainableMaterials.com, or speak with your Sustainable Materials account manager.

## **Product Testing Specifications**

Fire-rating: Class C (per ASTM E84-14); Flame Spread = 90; Smoke Developed = 400

**Pattern repeat:** No pattern repeat (non-woven)

